# **Detection Thresholds for Rare, Spectrally Unique Targets within Semiarid Rangelands**

Keith T. Weber and Fang Chen

# Abstract

Many factors influence classification accuracy, and this study assessed detection thresholds for various sub-pixel targets using QuickBird multispectral imagery. Six iterations of maximum-likelihood classification were used to determine classification accuracy for 100 spectrally unique targets randomly placed over a semiarid rangeland site. Error matrices were calculated using independent validation sites and producer's, user's, and overall accuracy, Kappa Index of Agreement, and transformed divergence were analyzed to compare the performance of each classification and determine detection thresholds. Results indicate a strong relationship between target size and classification accuracy ( $R^2 = 0.94$ ) as well as an increasingly prominent role played by training site selection as target size decreased. Strong spectral separability and good classification accuracies were achieved for targets >25 percent cover. Sub-pixel targets <25 percent in size were not detectable. This study highlights the effect of target size upon classification accuracy and has direct implications for invasive plant research and rare target detection.

# Introduction

Much has been written about the effects of various input parameters and processing decisions on classification accuracy. Researchers have investigated and described the (a) selection of appropriate classification algorithms (Foody and Arora, 1997), (b) effects of orthorectification (Cheng et al., 2003; Robertson, 2003; Toutin and Chenier, 2004; Wijnant and Steenberghen, 2004; Parcharidis et al., 2005), (c) effect of mis-registration between image layers (Townshend et al., 1992; Dai and Khorram, 1998; Stow, 1999; Roy, 2000; Verbyla and Boles, 2000; Wang and Ellis, 2005), (d) influence of spectral resolution (Mehner et al., 2004), (e) effects of coregistration between training sites and imagery (Weber, 2006; Weber *et al.*, 2008), (f) influence of atmospheric anomalies and correction processes (Lillesand and Kiefer, 2000), and (g) effects of training site purity relative to minimum ground cover threshold (Mundt et al., 2006). The result of these and other efforts has allowed geospatial scientists to construct a fairly complete error budget, and, thereby better understand and interpret image classification results. The latter topic is the focus of this paper with emphasis upon the detection threshold of sub-pixel targets.

In semiarid environments, the ability to detect sub-pixel targets is critical because landscape features such as sagebrush, shrubs, invasive weeds, and bare soil are frequently encountered in relatively small patches (i.e., 1 to 4 m<sup>2</sup>). Past research investigating detection limitations in remote sensing have frequently focused upon invasive plants and have reported detection thresholds from 10 percent cover (Parker-Williams and Hunt, 2002) to 40 percent cover (Glenn *et al.*, 2005; Weber *et al.*, 2006) for leafy spurge (*Euphorbia esula L.*), 30 percent cover for hoary cress (*Cardaria draba*) (Mundt *et al.*, 2006), and 20 percent cover for Rush skeletonweed (*Chondrilla juncea*) (Mundt *et al.*, 2006). In all cases, detection thresholds in these studies were determined using hyperspectral imagery with high spatial resolutions (e.g., 5 m).

The purpose of this research was to experimentally address the following questions related to the reliable detection (i.e.,  $\geq$ 75 percent overall accuracy; Goodchild et al., 1994) of spectrally unique, patchy, and rare targets within semiarid rangeland ecosystems: (a) what is the detection threshold (100 percent, 50 percent, 25 percent, 5 percent, and 1 percent of a pixel) that can be achieved using high spatial resolution multispectral imagery?, and (b) what is the impact of target size and site selection on sub-pixel target detection and classification accuracy? To address the former objective, various measures of classification accuracy and spectral separability were used including transformed divergence, error matrices, and the Kappa Index of Agreement (KIA). The latter objective (b) was addressed by exploring the variability of the above measures following six iterations of each classification trial and by examining the relationship between KIA and target size using linear regression analysis.

# Methods

## **Study Area**

The experiment was performed in sagebrush-steppe rangelands of southeast Idaho approximately 30 km south of Pocatello, Idaho at the O'Neal Ecological Reserve. This 50 ha site contains sagebrush-steppe upland areas located on lava benches. The Reserve receives <38 cm of precipitation annually (primarily in the winter) and is relatively flat, with a mean elevation of approximately 1,400 m (1,401 m to 1,430 m). The dominant plant species is big sagebrush (*Artemisia tridentata*) with various native and non-native grasses, including Indian rice grass (*Oryzopsis hymenoides*) and needle-and-thread (*Stipa comata*) present throughout the Reserve.

Photogrammetric Engineering & Remote Sensing Vol. 76, No. 11, November 2010, pp. 1253–1259.

0099-1112/10/7611–1253/\$3.00/0 © 2010 American Society for Photogrammetry and Remote Sensing

GIS Training and Research Center, Idaho State University, 921 S. 8th Ave., Stop 8104, Pocatello Idaho 83209-8104 (webekeit@isu.edu).

## **Field Data**

Throughout the study area, 20 target locations were randomly generated for each of five target sizes (n = 100)(Table 1). Bright blue tarps were placed at each of these

TABLE 1. PERCENT TARGET SIZE AND ACTUAL TARGET SIZE OF THE FIVE CLASSES USED IN THIS STUDY (NOTE: QUICKBIRD MULTISPECTRAL IMAGERY HAS A SPATIAL RESOLUTION OF  $2.40 \times 2.40$  m)

Target class (%)	Actual size (m)		
100 50 25 5 1	$\begin{array}{c} 2.40 \times 2.40 \\ 1.70 \times 1.70 \\ 1.20 \times 1.20 \\ 0.55 \times 0.55 \\ 0.24 \times 0.24 \end{array}$		

locations using the following set of criteria established for final placement in the field: (a) no part of the tarp was placed beneath vegetation, (b) tall vegetation (>1 m) that could cast a shadow on a portion of the tarp during image acquisition was not located near the tarps (+/-2 m), and (c) tarps were installed flat and horizontal to avoid deformation and changes in their apparent size within the imagery (Figure 1). All blue tarps were secured into the ground using four to eight 25 cm spikes approximately one month prior to the acquisition of remotely sensed imagery. The location of the tarps was recorded by occupying each site until 120 positions were acquired with a Trimble GeoXH GPS receiver. The averaged positions were post-process differentially corrected using data from five base stations each within 80 km of the Reserve. Resulting horizontal positional accuracy was +/- 0.3 m (95 percent confidence interval [CI]). An equal number of non-target points (n = 20) typical of the semiarid rangelands found at the Reserve (i.e., sites



dominated by big sagebrush) were randomly located throughout the study area and used as non-target training sites for all analyses and classifications. This was done to eliminate variability and bias due to disproportionate sample sizes. None of these points fell within 10 meters of a target site.

To better understand the results of subsequent classification, the spectral properties of the blue tarps targets were compared to the spectral properties of the common rangeland elements found at non-target sites using an Analytical Spectral Device (ASD) FieldSpecPro hand-held field spectroradiometer. Measurements were made during a sunny day (without clouds) at  $\pm 1$  hour of solar noon prior to image acquisition. For each target, between 15 and 25 spectral recordings were taken. Spectral comparison included blue tarps, bare soil, basalt, low sagebrush (*Artemisia arbuscula*), and big sagebrush (*Artemisia tridentata*).

#### Imagery

Standard QuickBird imagery (06 July 2009) was delivered by DigitalGlobe Corporation and projected into Idaho Transverse Mercator (NAD83) using nearest neighbor resampling to match the reference system of all other GIS data used in this study. The imagery was corrected for atmospheric effects using Chavez' Cos(t) model in IDRISI Taiga's ATMOSC module (Chavez, 1996). To improve georegistration of the imagery and co-registration between the imagery and ground truth locations (Weber et al., 2008) within the relatively small, flat study area, five permanent ground control platforms were used. Each platform was 2.4 m  $\times$  2.4 m in size and stood 1.2 m above the ground. During satellite image acquisition periods, highly reflective silver tarps were tightly secured to the platforms. The location of the platform's corners were recorded and processed in the same fashion as noted above. All five ground control platforms were used to georectify the QuickBird imagery using first order, affine transformation and nearest neighbor resampling (RMSE = 0.678).

## Analysis

To determine how small a target can be detected using high spatial resolution QuickBird multispectral imagery, a series of supervised presence/absence classifications were performed. To accomplish this, a geodatabase feature class containing 100 points representing the location of the blue tarp sites was created. This blue tarp feature class was randomly resampled without replacement to select 50 percent of the points in each target size class (n = 5 target size classes). This process was repeated six times (Table 1) to achieve a better estimation of classification accuracy (Weber and Langille, 2007). A single resampling event was used to randomly select 50 percent of the non-target training sites (n = 10). The remaining non-target sites were used as independent validation sites.

Bootstrap resampling was used in this study (Good, 2006) and for each target class ten points were randomly selected while the remaining ten points were reserved for validation. Ten non-target points were randomly selected and these same points were used in every classification trial while the remaining ten non-target points were used in all validations. To eliminate between-trial variability in the non-target class, iterative resampling of non-target sites was not performed.

The result of each resampling iteration produced two datasets for use in the classification process. The first dataset contained 20 training sites (ten blue tarp training site points per size class and ten non-target training site points), and the second contained 20 validation sites (ten blue tarp points per size class and ten non-target points). Each individual dataset was saved as a shapefile (n = 30; six

iterations of five size classes) and used to extract spectral signatures from QuickBird imagery (bands 1 through 4) at the locations of the training sites using IDRISI's MAKESIG module. Spectral signature extraction is a required step for maximum likelihood classification, and the resulting signature files statistically describe the spectral characteristics (minimum, maximum, mean, variance, and covariance) of those pixels identified as a target (i.e., the pixel contains a blue tarp) or non-target site (i.e., the pixel was a typical sagebrush-steppe rangeland site).

Spectral signatures were evaluated using the SEPSIG module of IDRISI which calculated a transformed divergence score (Richards and Jia, 2006). This score was used to indicate the separability of target and non-target sites for each spectral signature file (n = 30). Using a constant value of 2,000, spectral endmembers with separability values exceeding 1,600 were considered good candidates for successful differentiation during the classification process. Regardless of the separability score, all maximum likelihood trials were completed (n = 30).

A series of maximum likelihood classifications (Richards and Jia, 2006) were performed using IDRISI (MAXLIKE) and validated using the ERRMAT module, which calculates both a standard error matrix (Congalton and Green, 2009) and KIA (Cohen, 1960; Titus *et al.*, 1984; Foody, 1992; Monserud and Leemans, 1992). A cumulative error matrix (CEM) was developed by calculating the sum of each individual error matrix within each target size class. To determine the statistical difference among classification results, the CEM for a given target class was compared with the CEM of all other target size classes using variance of KIA by calculating a pairwise Z-statistic following Congalton and Green (2009) (Equation 1).

$$Z_{\text{pairwise}} = \frac{|K_1 - K_2|}{\sqrt{\operatorname{var}(K_1) + \operatorname{var}(K_2)}}$$
(1)

where  $K_1$  and  $K_2$  are the KIA's for error matrices 1 and 2 and  $var(K_1)$  and  $var(K_2)$  are estimates of variance for matrices 1 and 2. The  $Z_{pairwise}$  critical value at the 95 percent confidence interval is 1.96.

## **Results and Discussion**

## **Detection Threshold**

Transformed divergence separability scores of the spectral signature files for the 100 percent and 50 percent target classes (n = 6 signature files/target class) exceeded the threshold value of 1,600 ( $\overline{x}$ = 1998.8 and 1991.4 for the 100 percent and 50 percent classes, respectively), indicating the spectral signatures of those targets were statistically differentiable from the signatures of non-target sites. This result compares well with results from spectroradiometer analysis indicating the blue tarps were spectrally unique and separable from the adjacent matrix of features (Figure 2). Four of six (67 percent) signature files for the 25 percent target class had transformed divergence scores in excess of 1600 ( $\bar{x}$ = 1657.8), suggesting that under most instances targets with 25 percent cover were differentiable from non-target sites. Since the same non-target sites were used in all cases throughout this study, no effect can be inferred related to sub-sampling non-target sites. Rather, the observed difference in separability must be due to the specific combination of target training sites selected and the ground conditions within the remainder of the pixel not covered by the blue-tarp target. Only one of six signature files for both the 5 percent and 1 percent target cover



classes had transformed divergence scores exceeding 1600 ( $\bar{x}$ = 1172.0 and 1242.3 for the 5 percent and 1 percent classes, respectively) suggesting that a reliable classification at these cover levels was highly unlikely.

Following six iterations of maximum likelihood classifications, mean producer's accuracy for the 100 percent blue tarp target class was 75 percent, mean user's accuracy was 92 percent, and mean overall accuracy was 84 percent (Table 2). While all measures of accuracy were reduced for the 50 percent target class ( $\bar{x}$  overall accuracy = 70 percent) and even further reduced for the 25 percent target class ( $\bar{x}$  overall accuracy = 69 percent), the user's accuracy exceeded 80 percent in all cases (n = 6 classifications/target class). In contrast, the 5 percent and 1 percent target classes performed poorly with mean overall accuracies of 60 percent and 55 percent, respectively. In addition, both producer's and user's

TABLE 2. RESULTING MEASURES OF ACCURACY AND STANDARD ERROR (SE) FOR EACH BLUE TARP TARGET CLASS FOLLOWING SIX ITERATIONS OF MAXIMUM LIKELIHOOD CLASSIFICATION

Target Class	Producer's	Accuracy User	y User		
(%)		(%)	) Overall		
100 50 25 5 1	$\begin{array}{l} 0.75 \; (\mathrm{SE} = 0.05) \\ 0.50 \; (\mathrm{SE} = 0.08) \\ 0.45 \; (\mathrm{SE} = 0.03) \\ 0.45 \; (\mathrm{SE} = 0.11) \\ 0.22 \; (\mathrm{SE} = 0.08) \end{array}$	$\begin{array}{l} 0.92 \; (\mathrm{SE} = 0.03) \\ 0.83 \; (\mathrm{SE} = 0.08) \\ 0.87 \; (\mathrm{SE} = 0.05) \\ 0.64 \; (\mathrm{SE} = 0.09) \\ 0.65 \; (\mathrm{SE} = 0.15) \end{array}$	$\begin{array}{l} 0.84 \; (\mathrm{SE} = 0.02) \\ 0.70 \; (\mathrm{SE} = 0.05) \\ 0.69 \; (\mathrm{SE} = 0.02) \\ 0.60 \; (\mathrm{SE} = 0.04) \\ 0.55 \; (\mathrm{SE} = 0.07) \end{array}$		

accuracies for the 5 percent and 1 percent target classes were  $\leq 65$  percent in all cases corroborating well with the results of separability testing reported above.

## **Target Size and Site Selection**

Resulting mean KIA statistics reported a similar trend (Figure 3) of decreasing agreement with decreasing target size ( $R^2 = 0.94$ ) but also indicated that only the 100 percent target class resulted in substantial agreement (0.68) between known/modeled blue tarp target locations (Landis and Koch, 1977). Following Landis and Koch (1977) a fair level of agreement was found for the 50 percent and 25 percent target classes (0.40 and 0.38, respectively) while the mean KIA for the 5 percent and 1 percent target classes (0.20 and 0.10, respectively) were considered slight and similar to that expected from a chance (random) classification.

A pairwise Z-statistic was calculated to compare resulting error matrices between target classes (Table 3). These results indicate the 100 percent target class performed significantly better than all other target classes (z > 1.96). This may be attributable to the fact that the 100 percent target class had the potential to occupy full pixels homogenously, while all other target classes represented sub-pixel, heterogeneous classes. While the size of the blue tarps used for the 100 percent target class were equal to that of a QuickBird pixel, it is unlikely that each tarp was positioned to perfectly fit the extent of a pixel as acquired by the sensor. Consequently, it is more likely that individual training sites contained <100 percent cover by a blue tarp. This same problem is encountered regularly in all field studies and the results reported here are considered



with target class size. The line of best fit resulted in a coefficient of determination of 0.94

TABLE 3. PAIRWISE Z-STATISTIC RESULTS COMPARING VARIANCE OF KAPPA FROM CUMULATIVE ERROR MATRICES OF EACH TARGET CLASS. COMPARISONS WITH Z-SCORES >1.96 REPRESENTED SIGNIFICANTLY DIFFERENT CLASSIFICATION RESULTS

		Target Class (%)				
		100	50	25	5	1
Target Class (%)	100	_	2.84	3.16	4.56	7.46
	50		_	0.20	1.81	3.54
	25			_	1.67	3.47
	5				_	1.08
	1					—

applicable and valid. Indeed, target detection thresholds should be stated in terms of the size of the *in situ* target with full understanding that many training sites will be subdivided during image acquisition by the sensor.

The pairwise comparison between the 50 percent and 25 percent sub-pixel target classes showed no difference (z = 0.20) indicating these classifications performed similarly. The comparison between the 50 percent and 5 percent target classes had a z-score of 1.81 while the z-score comparing error matrices for the 25 percent and 5 percent target classes also showed no difference (z = 1.63). While the resulting classification accuracies reported in this study demonstrate the reliable detection of the 50 percent and even 25 percent target classes, the results of pairwise comparisons indicate that none of these classifications performed statistically different relative to one another.

Nearly all pairwise comparisons with the 1 percent target class were statistically significant (different) save for the comparison with the 5 percent target class (z = 1.08). In these cases, the overwhelming majority of each training site

classification. It is not surprising then, that pairwise comparisons with the 1 percent target class showed statistical differences (z > 1.96) as effectively no trace of the blue tarp's spectra may have been present and classification results followed a random distribution. The 5 percent target class performed similar to the 1 percent target class for many of the same reasons, resulting in pairwise comparisons that showed no difference. These results serve to emphasize the observation suggested by the results of separability testing; targets covering <25 percent of a pixel were unlikely to achieve reliable classification results under the conditions of this study. Goodchild *et al.* (1994) suggested 75 percent overall accuracy be used as a benchmark of classification reliabil-

pixel was occupied by non-target features and classification

results were similar to that expected by a chance (random)

accuracy be used as a benchmark of classification reliability and hence, detection. Under these guidelines, only the 100 percent target class achieved a reliable classification. However, the 50 percent and 25 percent target classes achieved a mean user's accuracy of >80 percent, albeit with producer's accuracies of only 50 percent and 45 percent, respectively ( $\overline{x}$  KIA = 0.40 and 0.38, respectively). These results suggest that while the 50 percent and 25 percent target classes were spectrally differentiable, other classification methods (e.g., linear spectral unmixing or classification and regression tree) may be required to achieve accurate classification results with multispectral sensors. A detailed study of the resulting error matrices indicates there was confusion between target and nontarget classes. This may be reduced however, by including simple band ratio layers (e.g., NDVI, MSAVI2), data reduction layers (e.g., principal components analysis image layers), or by excluding individual image bands where the greatest spectral similarity existed (e.g., the green and red bands in this study [Figure 2]).

This study was performed using QuickBird satellite imagery (2.4 mpp) as this sensor's spatial and spectral characteristics best facilitated the need to accurately locate rare and spectrally unique, sub-pixel targets. In semiarid environments, this ability is critical because landscape features such as sagebrush, shrubs, patches of invasive weeds, and patches of bare soil are frequently encountered at the same spatial order (i.e., 1 to 4 m). We believe these results may be applicable to other multispectral sensors regardless of the instrument's spatial resolution with 25 percent cover suggested as the detection threshold of these systems. However more research is required before such statements can be unequivocally made. To substantially improve the ability to detect small targets (i.e., <0.25) the use of hyperspectral imagery may be required (Parker-Williams and Hunt, 2002; Glenn et al., 2005) and/or techniques other than maximum likelihood to improve sub-pixel detection.

## Assessment of Error and Bias

All efforts were made to design and execute an experiment that would rigorously and empirically test the detection capabilities of multispectral imagery relative to rare and spectrally unique targets in semiarid ecosystems. The results reported here may vary somewhat if repeated in other ecosystems, but the ability to significantly reduce sub-pixel detection with multispectral sensors is not anticipated. In many ways, the results observed in this study may represent a best-case scenario as all targets were spectrally unique and both physically homogeneous (i.e., laid flat upon the earth with no neighboring shadow), and spectrally homogeneous (i.e.,  $\bar{x}$  standard deviation = 0.0001 for target spectra).

One potential error in this study relates to the exact placement of each target relative to the location and "edge" of each pixel acquired by the QuickBird sensor. It is possible, and indeed likely, that some of the targets were captured across pixels instead of within a single pixel as was assumed throughout the image analysis process. In these cases, target size was effectively reduced and the training site corrupted. For example, if a 50 percent blue tarp target site was captured across two pixels, the training site (located in the center of the target) might represent a 25 percent target spectrally as only a portion of reflectance from that tarp affected the training site pixel. This problem was most likely to have occurred with the larger target classes ( $\geq 50$ percent) and was less probable with smaller target classes (5 percent and 1 percent). This unavoidable error is not attributable to the experimental nature of this study but is common to all remote sensing studies and especially problematic with any study focusing upon patchy and rare target detection (e.g., the early detection of invasive weed infestations).

The number of samples used in this study presents another concern. To emulate the presence of rare targets, 100 blue tarps were prepared for this experiment, with 20 created for each target class. Of these 20, ten were randomly selected to be used for training sites while the remaining ten were used for independent validation in each trial, thus the sample size for each classification trial was 10. However, this bootstrap resampling technique was repeated six times to better capture the variability within the training site samples (Weber and Langille, 2007). While this remains a potential bias of this study, it should be understood that the spectral variance of the blue targets was very low ( $\overline{x}$  std. dev. = 0.0001;  $\bar{x}$  reflectance 0.07, 0.10, 0.06, and 0.26 for the blue, green, red, and NIR bands respectively) and the majority of variance was explained within the existing sample size. In addition, if the sample size were insufficient for this particular experiment, one would expect to see accuracy and KIA values that varied greatly between trials. This was not observed however, and indeed the standard error for all measures of classification accuracy were small for target classes  $\geq$ 25 percent (Table 2).

## Conclusions

This study sought to experimentally determine the detection capabilities of multispectral imagery and was not designed to develop and test new algorithms for sub-pixel classification. For this reason, the authors used a common classification technique (maximum likelihood) and only basic (atmospherically corrected) image bands (i.e., blue, green, red, and near infra-red). To address the objectives of this study, six iterations of maximum-likelihood classification were used to determine classification accuracy for 100 spectrally unique targets randomly placed over a semiarid rangeland site. Error matrices were calculated using independent validation sites and producer's accuracy, user's accuracy, overall accuracy, KIA, and transformed divergence were analyzed to compare the performance of each classification and determine detection thresholds. The results of this study suggest training site selection (both initial site selection in the field and the selection of sites during resampling operations in the laboratory) has significant effect on classification accuracy. This effect became more pronounced as target size decreased, as the standard deviation of overall accuracy increased from 0.06 (100 percent target class) to 0.16 (1 percent target class).

This study demonstrated (a) the applicability of transformed divergence separability scores as an indicator of potential classification success, (b) an empirical relationship ( $R^2 = 0.94$ ) between target size and classification accuracy, and (c) the limitation of multispectral imagery for sub-pixel target detection. Regarding the latter, it appears the detection threshold of spectrally unique targets is approximately 25 percent cover within semiarid rangelands. This has direct implication for invasive plant research and rare target detection as targets such as leafy spurge or purple loosestrife may be undetectable until an infestation covers 25 percent or more of a pixel. If the results and relationships demonstrated in this study transfer directly to other multispectral sensors and furthermore, if Landsat imagery ( $30 \times 30$  m pixels) were used, then weed infestations would need to be 225 m<sup>2</sup> in area before the infestation would be detectable. This is problematic as land managers rely upon early detection for effective control and eradication of weeds.

While the classification results reported in this study for both the 50 percent and 25 percent target classes were not ideal (overall accuracy was <75 percent), the user's accuracy was satisfactory (>80 percent). To substantially improve the ability to detect proportionally small targets (<0.25 pixel), the use of hyperspectral imagery may be required and/or techniques other than maximum likelihood (e.g., linear spectral unmixing or classification and regression trees) to improve sub-pixel detection.

## Acknowledgments

This study was made possible by a grant from the National Aeronautics and Space Administration Goddard Space Flight Center (NNX08AO90G). Idaho State University (ISU) would also like to acknowledge the Idaho Delegation for their assistance in obtaining this grant.

#### References

- Chavez, P.S., 1996. Image-based atmospheric corrections: Revisited and improved, *Photogrammetric Engineering & Remote Sensing*, 62 (9):1025-1036.
- Cheng, P., T. Toutin, Y. Zhang, and M. Wood, 2003. QuickBird -Geometric correction, path and block processing and data fusion, *Earth Observation Magazine (EOM)*, May, pp. 24-30.
- Cohen, J., 1960. A coefficient of agreement for nominal scales, Educational and Psychological Measurement, 20(1):37-46.
- Congalton, R.G., and K. Green, 2009. Assessing the Accuracy of Remotely Sensed Data: Principles and Practices, CRC Press, Inc., Boca Raton, Florida, 183 p.
- Dai, X., and S. Khorram, 1998. The effects of image misregistration on the accuracy of remotely sensed change detection, *IEEE Transactions on Geoscience and Remote Sensing*, 36:1566-1577
- Foody, G.M., 1992. On the compensation for chance agreement in image classification accuracy assessment, *Photogrammetric Engineering* & *Remote Sensing*, 58(10):1459-1460.
- Foody, G.M., and M.K. Arora, 1997. An evaluation of some factors affecting the accuracy of classification by an artificial neural network, *International Journal of Remote Sensing*, 18(4):799-810.
- Glenn, N.F., J.T. Mundt, K.T. Weber, T.S. Prather, L.W. Lass, and J. Pettingill, 2005. Hyperspectral data processing for repeat detection of small infestations of leafy spurge, *Remote Sensing* of Environment, 95(3):399-412.
- Good, P.I. 2005. Resampling methods: A practical guide to data analysis, Third edition, Birkhauser, 218 p.
- Goodchild, M.F., G.S. Biging, R.G. Congalton, P.G. Langley, N.R. Chrisman, and F.W. Davis, 1994. *Final Report of the Accuracy Assessment Task Force*, California Assembly Bill AB1580, Santa Barbara, University of California, National Center for Geographic Information and Analysis (NCGIA).
- Landis, J.R., and G.G. Koch, 1977. The measurements of observer agreement for categorical data, *Biometrics*, 33 (1):159-174.
- Lillesand, T.M., and R.W. Kiefer, 2000. *Remote Sensing and Image Interpretation*, Fourth Edition, John Wiley and Sons, New York.

Mehner, H., M. Cutler, D. Fairbairn, and G. Thompson, 2004. Remote sensing of upland vegetation: The potential of high spatial resolution satellite sensors, *Global Ecology and Biogeography*, 13(4):359-369.

- Monserud, R., and R. Leemans, 1992. Comparing global vegetation maps with the kappa statistic, *Ecological Modeling*, 62(4):275-293.
- Mundt, J.T., N.F. Glenn, K.T. Weber, and J. Pettingill, 2006. Determining target detection limits and accuracy delineation using an incremental technique, *Remote Sensing of Environment*, 105(1):34-40.
- Parcharidis, I., M. Foumelis, E. Papageorgiou, M. Segou, and V. Sakkas, 2005. Orthorectification and assessment of QuickBird imagery using D-GPS measurements over Paros urban area, *Proceedings of the International Society for Photogrammetry and Remote Sensing 2005 Joint Conference*, Tucson, Arizona, USA.
- Parker-Williams, A., and E.R. Hunt, 2002. Estimation of leafy spurge cover from hyperspectral imagery using mixture tuned matched filtering, *Remote Sensing of Environment*, 82(2):446-456.
- Richards, J.A., and X. Jia, 2006. *Remote Sensing Digital Image Analysis*, Fourth edition, Springer-Verlag, Berlin, 439 p.
- Robertson, B.C., 2003. Rigorous modeling and correction of Quick-Bird imagery, *Proceedings of the IEEE International Geoscience and Remote Sensing Symposium (IGARSS '03)*, Toulouse, France, pp. 797-802.
- Roy, D.P., 2000. The impacts of misregistration upon composited wide field of view satellite data and implications for change detection, *IEEE Transactions on Geoscience and Remote Sensing*, 38(4):2017-2032.
- Stow, D.A., 1999. Reducing the effects of misregistration on pixellevel change detection, *International Journal of Remote Sensing*, 20(12):2477-2483.
- Titus, K., J.A. Mosher, and B.K. Williams, 1984. Chance-corrected classification for use in discriminant analysis: Ecological applications, *The American Midland Naturalist*, 111(1):1-7.
- Toutin, T., and R. Chenier, 2004. GCP requirement for highresolution satellite mapping, *Proceedings of the International*

Society for Photogrammetry and Remote Sensing 2004 Congress, Istanbul, Turkey.

- Townshend, J.R.G., C.O. Justice, C. Gurney, and J. McManus, 1992. The impact of misregistration on change detection, *IEEE Transactions on Geoscience and Remote Sensing*, 30 (5):1054-1060.
- Verbyla, D.L., and S.H. Boles, 2000. Bias in land cover change estimates due to misregistration, *International Journal of Remote Sensing*, 21(18):3553-3560.
- Wang, H., and E.C. Ellis, 2005. Image misregistration error in change measurements, *Photogrammetric Engineering & Remote Sensing*, 71(9):1037-1044.
- Weber, K.T., 2006. Challenges of integrating geospatial technologies into rangeland research and management, *Rangeland Ecology* and Management, 59(1):38-43.
- Weber, K.T., and J. Langille, 2007. Improving classification accuracy assessments with statistical bootstrap resampling techniques, *GIS Science and Remote Sensing*, 44 (3):237-250.
- Weber, K.T., N.F. Glenn, J.T. Mundt, and B. Gokhale, 2006. A comparison between multi-spectral and hyperspectral platforms for early detection of leafy spurge in southeastern Idaho, *Final Report: Detection, Prediction, Impact, and Management of Invasive Plants Using GIS* (K.T. Weber, editor) pp. 185-196, URL: http://giscenter.isu.edu/research/techpg/ nasa\_weeds/pdf/multi\_vs\_hyper.pdf (last date accessed: 10 August 2010).
- Weber, K.T., J. Theau, and K. Serr., 2008. Effect of co-registration error on patchy target detection using high-resolution imagery, *Remote Sensing of Environment*, 112(3):845-850.
- Wijnant, J., and T. Steenberghen, 2004. Per-parcel classification of urban IKONOS imagery, Proceedings of 7<sup>th</sup> AGILE Conference on Geographic Information Science, Heraklion, Greece, pp. 447-455.
- (Received 13 November 2009; accepted 06 April 2010; final version 13 April 2010)